

> PRINT > COPY > SCAN > FAX

TASKalfa 4053ci

COLOUR MULTIFUNCTIONAL FOR A4/A3 (SRA3) FORMAT

# SOLVE DOCUMENT NEEDS SECURELY



With advanced security measures and a key focus on usability, the new TASKalfa 4053ci is the ideal solution for office document requirements. Vibrant colour ensures high quality printing whilst also offering a flexible approach to paper-handling and finishing, meaning that the multifunctional product is the complete solution to provide an efficient way to print, copy, scan and much more. Relying on an award-winning engine, quality and consistency is assured. A touch-screen panel provides enhanced usability which enables users more flexibility with their documents. These features come together to provide a well rounded multifunctional product perfect for the needs of businesses of all sizes in a variety of industries.

- > Up to 40/20 pages A4/A3 per minute in colour
- > Outstanding image quality due to advanced colour technology
- > User friendly and intuitive 10.1 inch operation panel
- > Advanced paper handling from A6 up to SRA3 for up to 7,150 sheets
- > Great range of high speed colour scanners and productive finishing ontions
- > High-level build in security features including data encryption, Trusted Platform Module, Secure Boot and Run Time Integrity Check
- > Long-life components provide exceptional efficiency, reliability and
- > Optional Fiery controller for highest productivity and colour quality



Securing your printing environment should be just as important as keeping your company doors locked. The new TASKalfa 4053ci is ready to meet today's security demands by including outstanding security features as the standard.

**Technology:** KYOCERA TASKalfa Laser Colour, HyPAS solution platform

**Touch panel size:** 256.5 mm (10.1 inch) full-colour touch panel display, speaker for job notification, 15° - 90° swivel

Engine speed (pages per minute): Duplex print speed: 40 ppm A4; Duplex copy speed: 40 ppm, A4 Resolution: 4800dpi equivalent x 1200dpi (print), 600 x 600 dpi (scan/copy)

Warm-up time from power on: Approx. 17 seconds or less Time to first print: 5.1 / 6.5 seconds or less in b/w / colour

Time to first copy: 5.1/ 7.4 seconds or less in b/w / colour (DP); 4.5/ 5.9 seconds or less in b/w / colour (Platen) CPU: QorlQ T1024 (Dual Core) 1.2GHz

Memory (standard max.): 4GB RAM + 8GB SSD +

Standard interface: Standard interface: USB 3.0 (Super-Speed USB), 4 x USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT, IPv6, IPv4, IPSec, 802.3az support), optional Wi-Fi (IEEE 802.11b/g/n), 2 eKUIO slots, for optional internal print server or for op tional fax system, slot for optional Wireless LAN, Slot for optional SD Card, NFC tag

Dimensions (W x D x H): Main unit: 602 x 665 x 790 mm

Weight: Main unit: Approx. 95 kg Power source: AC 220 V ~ 240 V, 50/60 Hz Power consumption:

Printing: 770 W Copying: 770 W Low power mode: 50 W

Ready mode: 60 W Sleep mode: 0.7 W Noise (sound pressure level ISO 7779 measurement

distance of 1 meter): Copying/Printing: 67 dB(A) Stand-by: 35 dB(A) LpA

Safety standards: 6S, TÜV, CE.
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

## PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions. Input capacity:

Multipurpose tray: 150 sheets, 52 – 300 g/m² (Banner 136 – 163 g/m²), A6R – SRA3 (320 x 450 mm), Custom (98 x 148 to 297 x 457.2 mm), Banner max. 304.8 x 1,220 mm; 148 to 297 X 457.2 mm), batiner max. 304.8 X 1,220 Standard universal paper cassette: 2 x 500 sheets, 52–300 g/m², upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 **Duplex unit:** Duplex as standard supports A6R—SRA3, 64—256 g/m²

Output capacity: Standard 500 sheets face-down, max. output capacity 4,300 sheets

Controller language: PRESCRIBE Emulations: PCL6 (PCL5c/PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and

Openating systems: All current Windows operating systems, Mac OS X Version 10.9 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec,SNMPv3, quick copy, proof and hold, private print, job storage functionality

**Mobile printing support:** KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi,

Google cloud print

# **COPY FUNCTIONS**

Max. original size: A3 / Ledger Continuous copying: 1–9999 Zoom range: 25–400% in 1% steps Preset magnification ratios: 5R/5E Image adjustments: Text + photo, text, photo,

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, image repeat, page numbering, cover mode, booklet copy, interrupt copy, form overlay, margin shift, auto cassette change, skip blank page, ID copy

Functionality: Scan to e-mail. Scan to FTP. Scan to SMB. Scan to USB Host, Scan to box, Network TWAIN, WIA/WSD scar

WIA/WSD SCAII
SCAN speed: 220 images per minute (300 dpi, A4 duplex, with DP-7130) in b/w and colour
Scan resolution: 600dpi x 600dpi , 400dpi x 400dpi , 200dpi x 400dpi , 200dpi x 200dpi x 200dpi , 200dpi x 100dpi , 200dpi x 20

200dpi x 100dpi; 256 greyscales per colour Max. scan size: A3, Ledger Original recognition: Tlext, photo, text + photo, Light Text / Fine Line, optimised for OCR File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u, Searchable PDF(option), MS Office file(option)

Compatibility: ITII-T Super G3 Modem speed: Max. 33.6 kbps Scanning speed: 2.0 seconds or less Transmission speed: Max. 3 seconds (JBIG) Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: Network faxing, rotate transmission, rotate reception, encrypted transmission and reception, duplex fax reception, memory reception, mailbox, remote diagnostics, polling transmission and reception, broad-cast, Optional Internet-fax, dual fax with second fax system 12

# CONSUMABLES

Average continuous toner yield in accordance with 5%

coverage A4.

TK-8525K Toner-Kit: Toner black for 30,000 page: TK-8525C, TK-8525M, TK-8525Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages WT-8500 Waste Toner Bottle: 40,000 shets (in accord-

ance with 5% coverage b/w:colour = 7:3)

Staple cartridge: SH-10 5000 x 3 staples, for DF-7100, DF-7120 and BF-730 SH-12 5000 x 3 staples, for DF-7110

Fax System 12 Internet Fax Kit (A)

**SH-14** 5000 x 5 staples, for DF-7130

Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR), convert to PDF or MS Office (docx, xlsx, pptx)

Printing System 15: Fiery Controller
Printing System Interface Kit 15: Interface board for Fiery Controlle

Paper handling
DP-7100 Document processor: (Reversing), 140 sheets,
35 – 160 g/m² (simplex), 50–120 g/m² (duplex), A6R – A3, Banner up to 1,900 mm

**DP-7110 Document processor:** (one-path duplex scanning) 270 sheets at 50 - 80 g/m²; 35 - 220 g/m² (simplex), 50 - 220 g/m² (duplex), A6R - A3, Banner up to 1,900 mm DP-7130 Document processor: (one-path duplex scanning with ultrasonic sensor), 270 sheets at 50 - 80 g/m², 35-220 g/m² (simplex), 50-220 g/m² (duplex),

DT-730(B) Document tray
PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m²,

PF-7110 Paper feeder: 2x 1,500 sheets, 52 - 300 g/m², A4,

**PF-7120 A4 side Deck:** 3,000 sheets, 60 – 300 g/m², A4, B5 **DF-7100 Inner finisher:** 500 sheets A4, 52–300 g/m², A6R–SRA3, Stapling up to 50 sheets A4 or

30 sheets A3 at 3 positions

30 Sheets A3 at 3 positions
DF-7110\* Document finisher + AK-7110:
Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4;
52 – 300 g/m²; max. A6R – SRA3
Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions
DF-7120\* Document finisher + AK-7110:

1,000 sheets A4, 52–300 g/m², AGR – SRA3, Stapling up to 50 sheets A4 or 30 sheets A3 at 3 positions **DF-7130' Document finisher + AK-7110:** 

DI-7/130 DOCUMENT INISING F A AK-7110: Main tray: 4,000 sheets A4; Sub tray: 200 sheets A4, 52–300 g/m², A6R–SRA3; Stapling up to 100 sheets A4 or 50 sheets A3 at 3 positions AK-7110 Attachment kit for DF-7110, DF-7120 and DF-7130 100 sheets, 52–300 g/m², A6R–SRA3, \*Bridge unit AK-7110 is required when using a finisher PH-7C/PH-7D Punch unit for DF-7110/DF-7120/DF-7130: 2-hole/4-hole/Swedish type 60–256 g/m² ASR–A3

PH-7C/PH-7D Punch unit for DF-7110/DF-7130: 2-hole/4-hole/Swedish type, 60 – 256 g/m², A5R – A3 MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m² BF-730 Booklet and tri-folding unit for DF-7110 Half-folding: 52–256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60 – 90 g/m²) Non-staple folding: Max. 5 sheets (60–90 g/m²) Tri-folding: Max. 5 sheets (60–90 g/m²), 3 sheets (91–105 g/m²)

(91-105 g/m²) **BF-9100 Booklet and tri-folding unit for DF-7130:**Half-folding: 52-256 g/m², A3, B4, A4R

Booklet: Max 20 sheets (80 pages, 60-90g/m²) or Max 13 sheets (52 pages 91-105g/m²)

Non-staple: Max 5 sheets (60-90g/m²) or Max 3 sheets (91-

105g/m<sup>2</sup>) Tri-folding: Max 5 sheets(60-90g/m2) or Max 3 sheets(91-

105g/m²) JS-7100 Job separator:

100-sheet internal job separator, 52 - 300 g/m2, A5R - SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher, Swedish type

Swedish type

Banner Guide 10: Banner paper feeding guide, 10 sheets

Keybordholder 10

NK-7120 Numeric keypad

USB IC Card Reader + Card Authentication Kit (B):

Support for various authentication keys available. The card holder is standard

UG-33 AC: ThinPrint support
UG-34 AC: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface

IB-35: Direct Wi-Fi Interface

IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1.000 BaseT

IB-51: Wireless LAN Interface (802.11b/g/n)
Platen cover (E)

CB-7100W: Wooden cabinet CB-7110M: Metal cabinet















KYOCERA Document Solutions Europe B.V. - Bloemlaan 4 -2132NP Hoofddorp - The Netherlands Tel +31 (0)20 6540 000 - Fax +31(0)20 653 1256 www.kyoceradocumentsolutions.eu - info@deu.kyocera.com

KYOCERA Document Solutions Inc. - 2-28, 1-Chome - Tamatsukuri Chuo-Ku - Osaka 540-8585 - Japan - www.kyoceradocumentsolutions.com

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

